

Technical Bulletin

ATTENTION All Fire Alarm System Installers & Designers

January 29, 2015

From: Crown Supply

Subject: FireLite MS-9050UD/Low Frequency Horn Advisory

Please be advised:

The FireLite MS-9050UD has only 2.10 amps available for Notification Appliance and Remote Annunciators added to this system. The new LOW FREQUENCY horns draw a lot more current than the previous MINI HORNS that we used.

- WHEELOCK LLFHNR-N draws .113 amps each
- SYSTEM SENSOR HR-LF draws .153 amps each

What this means:

If you are using a MS-9050UD with LOW FREQUENCY HORNS you can only have:

13 SYSTEM SENSOR HR-LF ($2.10\text{amps} \div .153 = 13.725$)

18 WHEELOCK LLFHNR-N ($2.10\text{amps} \div .113 = 18.584$)

This is in addition to any horn strobes and WP Horn Strobes that the customer will also need.

Please be aware of the limitations of the MS-9050UD Notification Appliance Circuits when loading them with LOW FREQUENCY Horns!

The FireLite MS-9200UDLS has 3 amps available out of the box and it can be increased to 6 amps with the addition of the XRM-24B transformer.

Regards,

Crown Supply Co.
26 Silver Spring Street
Providence, RI 02904

401-861-6329

sales@crownsupply.com

